

Technical Data Sheet

Page 1 of 1

- Properties:** AKEMI® Coloring Concentrates liquid / Coloring Pastes are concentrates in different color shades. The products are characterized by the following properties:
- easy coloring of adhesives based on polyester, epoxyacrylate and PUR
 - the liquid consistency (of concentrates) makes it easier to mix with liquid products
 - matching the color of the adhesive to many common stone colors
 - balanced pigment concentration, thus easy adjustment of different color shades and high coverage
 - extremely UV- and light-resistant pigments, i.e. no fading
 - no deterioration of the properties of the colored adhesives
- Application Area:** AKEMI® Coloring Concentrates liquid / Coloring Pastes are used for coloring Marble Filler 1000, Marble Filler Super, MS 76, PLATINUM P+ (epoxyacrylate adhesive), Polishing Line Adhesive RAPID and EVER-CLEAR (PUR adhesive). Thus, the color of the adhesive can be adjusted to the respective stone color.
- Instructions for Use:**
1. Add maximum 5% of AKEMI® Coloring Concentrate liquid / Coloring Paste to the adhesive to be colored, depending on the color of the concentrate and the stone.
 2. Mix well until a homogenous shade of color is achieved.
- Special Notes:**
- Use afin® Liquid Glove to protect your hands.
 - Hardener to be added after the color had been adjusted.
 - For proper waste disposal, the container must be completely emptied.
- Technical Data:** Colors: red, redbrown, white, black, ochre, green, brown, blue
Coloring Concentrates: additionally beige, grey
- Storage:** If stored in dry and cool condition (41-77°F) in its closed original container at least 3 years from production.
- Health & Safety:** Read Safety Data Sheet before handling or using this product.
- Important Notice:** The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.