
SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: XtraBond 50 Clear Siliconized Acrylic Sealant

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Sealant

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Premier Building Solutions, Inc.
480 Nova Dr.
Massillon, OH 44646

Telephone Number: 1-(330)-244-2907

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: CHEMTREC 1-800-424-9300 (US and Canada)
INTERNATIONAL + 1-703-527-3887

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR 1910.1200 (OSHA HAZCOM2012)

Serious Eye Irritation

Category 2A

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:
DANGER!

2.2b HAZARD STATEMENTS
Causes serious eye irritation

2.2c HAZARD PICTOGRAMS



2.2d PRECAUTIONARY STATEMENTS

i. PREVENTION	Wash hands thoroughly after handling. Do not breathe vapors/fumes. Do not eat, drink or smoke while using this product. Use in a well ventilated area. Wear
----------------------	---

SAFETY DATA SHEET

	impervious gloves/protective clothing/eye protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Contaminated work clothing must not be allowed out of the workplace.
ii. RESPONSE	If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell. If exposed or concerned: Get medical advice/attention.
iii. STORAGE	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
iv. DISPOSAL	Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED

Not Applicable

2.3b UNKNOWN ACUTE TOXICITY

<1% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Chemical Name	CAS Number	Weight %
Acrylic Polymers	Proprietary	40 – 70%*
Polyethylene glycol octylphenyl ether	9036-19-5	0.5 – 1.5%*
Ethylene Glycol	107-21-1	0.1 – 1.0%*
Ammonia	7664-41-7	0.1 – 1.0%*

**Inhalation of particulates unlikely due to product's physical state.

*Means that the component will fall into one of the ranges specified due to batch-to-batch variability and to protect Confidential Business Information.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention immediately.

SAFETY DATA SHEET

- Skin Contact:** In case of contact, immediately flush skin with plenty of soap and water. For minor skin contact, avoid spreading material on unaffected skin. If skin irritation or rash occurs: get medical attention/advice. Take off contaminated clothing and wash before reuse.
- Inhalation:** If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin Contact:	May cause skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause an allergic skin reaction.
Inhalation:	May cause respiratory tract irritation. May cause damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.
Ingestion:	May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

- Note to Physicians:** Symptoms may not appear immediately.
- Specific Treatments:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Not Flammable/Not Combustible by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:

SAFETY DATA SHEET

Treat for surrounding material.

5.2b. Unsuitable Extinguishing Media:

Water

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:

By heating and fire, harmful vapors/gases may be formed. Nitrogen Oxides(corrosive)

5.3b. Explosion Data

i. Sensitivity to Mechanical Impact:

Not Available

ii. Sensitivity to Static Discharge:

Not Available

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear(full bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Methods for Containment: Recover all usable material. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Dispose of unwanted material properly in accordance with all local, regional, national and international regulations.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Use in well-ventilated areas. Wear impervious gloves and eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe vapors/fumes. Do not take internally.

General Hygiene Advice: Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

SAFETY DATA SHEET

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Store locked up. Keep out of the reach of children. Keep container tightly closed. Store at room temperature and keep containers closed when not in use.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETER

Exposure Guidelines:

Occupational Exposure Limits		
Chemical Name	OSHA-PEL	ACGIH-TLV
Acrylic Polymers	Not Available	Not Available
Polyethylene glycol octylphenyl ether	Not Available	10 mg/m ³
Ethylene Glycol	50 ppm 125 mg/mg ³	100 mg/m ³
Ammonia	50 ppm	25 ppm

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

- i. **Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]
- ii. **Skin Protection:**
 - 1. **Hand Protection:** Wear impervious gloves, such as nitrile.
 - 2. **Body Protection:** Wear suitable protective clothing.
- iii. **Respiratory Protection:** A NIOSH approved respirator or filtering face piece, such as N95, is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. **General Health and Safety Measures:** Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Clear Paste
--	-------------

SAFETY DATA SHEET

Odor:	Latex
Odor Threshold:	Mild
pH:	Not Available
Melting point/Freezing point:	Not Available
Initial boiling point and boiling range:	Not Available
Flash point:	Not Available
Evaporation rate (Water=1):	Not Available
Flammability:	Not Flammable/Not Combustible
Upper Flammability/Explosive Limit:	Not Available
Lower Flammability/Explosive Limit:	Not Available
Vapor Pressure	Not Available
Vapor Density:	Not Available
Relative Density:	1.05 – 1.20 g/mL
Solubility in Water:	Insoluble
Partition coefficient: n-octanol/water:	Not Available
Auto-ignition temperature:	Not Available
Decomposition Temperature:	Not Available
Viscosity (cps):	Not Available
VOC Content:	<30 g/L

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

10.5. INCOMPATIBLE MATERIALS

Strong oxidizing agents.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Carbon oxides.

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

SAFETY DATA SHEET

- Eye Contact:** Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Skin Contact:** May cause skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause an allergic skin reaction.
- Inhalation:** May cause respiratory tract irritation. May cause damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.
- Ingestion:** May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

Acute Toxicity (ATE _{mix} = 5,514 mg/kg)		
Chemical Name	LC50	LD50
Acrylic Polymers	Not Available	Oral: 6,450 mg/kg, rat
Polyethylene glycol octylphenyl ether	Not Available	Oral: >16,000 mg/kg, rat
Ethylene Glycol	Not Available	Oral: 1,616 mg/kg, rat
Ammonia	2000 ppm, 4hrs	Oral: 350 mg/kg, rat

Carcinogenicity	
Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)
Acrylic Polymers	Not Listed
Polyethylene glycol octylphenyl ether	Not Listed
Ethylene Glycol	Not Listed
Ammonia	Not Listed

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM	
Skin Corrosion/Irritation:	May cause skin irritation
Serious Eye Damage/Irritation:	Causes serious eye irritation
Respiratory Sensitization:	Not Classified
Skin Sensitization:	Not Classified
STOT-Single Exposure:	May cause respiratory irritation
Aspiration Hazard:	Not Classified
LONG-TERM	
Carcinogenicity:	Not Classified
Germ Cell Mutagenicity:	Not Classified
Reproductive Toxicity:	Not Classified
STOT-Repeated Exposure:	Not Classified
Synergistic/Antagonistic Effects:	Not Classified

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

SAFETY DATA SHEET

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity		
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours
Acrylic Polymers	>100 mg/L, Daphnia magna	>1,000 mg/L, Oncorhynchus mykiss
Polyethylene glycol octylphenyl ether	>2,500 mg/L Daphnia magna	440 mg/L, Pimephales promelas
Ethylene Glycol	>100 mg/L, Daphnia magna	72,680 mg/L, Pimephales promelas
Ammonia	0.53 ppm, Daphnia magna	300 µg/L, Hypophthalmichthys nobilis

12.2. PERSISTENCE AND DEGRADABILITY

Not Available

12.3. BIOACCUMULATIVE POTENTIAL

Not Available

12.4. MOBILITY IN SOIL

Not Available

12.5. OTHER ADVERSE EFFECTS

Not Available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS

Not Available

Section 14: TRANSPORT INFORMATION

DOT (U.S.)	TDG (CANADA)	IATA
UN NUMBER: Not Regulated	UN NUMBER: Not Regulated	UN NUMBER: Not Regulated
UN PROPER SHIPPING NAME: Not Regulated	UN PROPER SHIPPING NAME: Not Regulated	UN PROPER SHIPPING NAME: Not Regulated
TRANSPORT HAZARD CLASS (ES): Not Regulated	TRANSPORT HAZARD CLASS (ES): Not Regulated	TRANSPORT HAZARD CLASS (ES): Not Regulated
PACKING GROUP (if applicable): Not Regulated	PACKING GROUP (if applicable): Not Regulated	PACKING GROUP (if applicable): Not Regulated

SUMMARY: Product is NOT regulated under DOT/TDG and other transportation regulations.

14.1. ENVIRONMENTAL HAZARDS

SAFETY DATA SHEET

Not Available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not Available

14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL


Canada: This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

US: SDS prepared pursuant to the Hazard Communication Standard (29 CFR 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

CHEMICAL NAME	SARA TITLE III			
	SECTION 302 (EHS) TPQ (LBS)	SECTION 304 EHS RQ (LBS)	CERCLA RQ (LBS)	SECTION 313 (TRI)
Acrylic Polymers	Not Listed	Not Listed	Not Listed	Not Listed
Polyethylene glycol octylphenyl ether	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene Glycol	Not Listed	Not Listed	5000 lbs	Listed
Ammonia	Not Listed	Not Listed	Not Listed	Listed

15.3. US STATE RIGHT TO KNOW LAWS:

California Proposition 65:	 WARNING: This product can expose you to chemicals including acetaldehyde, which is known to the State of California to cause cancer, and ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Other U.S. States "Right to Know" Lists:	Acrylic Polymers: CAS#N/A Polyethylene glycol octylphenyl ether: CAS#9036-1-9-5 Ethylene Glycol: CAS#107-21-1 Ammonia: CAS#7664-41-7 Distillates (petroleum), solvent-dewaxed heavy paraffinic: CAS#64742-65-0


15.4. GLOBAL INVENTORIES

Chemical Name	USA TSCA	Canada DSL/NDSL
Acrylic Polymers	Yes	DSL
Polyethylene glycol octylphenyl ether	Yes	DSL
Ethylene Glycol	Yes	DSL
Ammonia	Yes	DSL

SAFETY DATA SHEET












15.5. NFPA AND HMIS RATINGS:

HEALTH HAZARD 4 EXTREME - Highly toxic - May be fatal on short-term exposure. 3 SERIOUS - Toxic - Full protective suit and breathing apparatus should be worn. 2 MODERATE - Breathing apparatus and face mask must be worn. 1 SLIGHT - Breathing apparatus may be worn. 0 MINIMAL - No precautions necessary.	FLAMMABILITY HAZARD 4 EXTREME - Extremely flammable gas or liquid. Flash Point below 73°F. 3 SERIOUS - Flammable. Flash Point 73°F to 300°F. 2 MODERATE - Combustible. Requires moderate heating to ignite. Flash Point below 200°F. 1 SLIGHT - Slightly combustible. Requires strong heating to ignite. 0 MINIMAL - Will not burn under normal conditions.
INSTABILITY HAZARD 4 EXTREME - Explosive at room temperature. 3 SERIOUS - May detonate if shocked or heated under confinement or mixed with water. 2 MODERATE - Unstable. May react with water. 1 SLIGHT - May react if heated or mixed with water. 0 MINIMAL - Normally stable. Does not react with water.	SPECIFIC HAZARD OXIDIZER OX ACID AC ALKALI AL CORROSIVE CO Use NO WATER W RADIATION RA



HMIS

Hazard Index	
4	Severe Hazard
3	Serious Hazard
2	Moderate Hazard
1	Slight Hazard

2 HEALTH	PROTECTIVE EQUIPMENT INDEX	
0 FLAMMABILITY	A 	G 
0 REACTIVITY	B 	H 
X PERSONAL PROTECTION	C 	I 
	D 	J 
	E 	K 
	F 	X Ask your supervisor for special handling instructions.

15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65
OSHA (O)	Occupational Safety and Health Administration
ACGIH (G)	American Conference of Governmental Industrial Hygienists <ul style="list-style-type: none"> A1 – Confirmed human carcinogen A2 – Suspected human carcinogen A3 – Animal carcinogen A4 – Not classifiable as a human carcinogen A5 – Not suspected a human carcinogen
IARC (I)	International Agency for Research on Cancer <ul style="list-style-type: none"> 1 – The agent (mixture) is carcinogenic to humans 2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.



Conforms to OSHA HazCom 2012 Standard and WHMIS 2015

SAFETY DATA SHEET

	<ul style="list-style-type: none">• 2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.• 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.• 4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.
NTP (N)	National Toxicology Program <ul style="list-style-type: none">• 1 – Known to be carcinogens• 2 – Reasonably anticipated to be carcinogens

Section 16: OTHER INFORMATION

Date of Preparation: May 12, 2020

Version: 1.1

Revision Date: October 30, 2023

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by: Premier Building Solutions, Inc.
Phone: (330)-244-2907
www.premierbuildingsolutions.net

End of Safety Data Sheet