

Rev. 01/2015

TECHNICAL DATA SHEET (TDS)

SUPERLUX

ID Product Code 015

Pag | 1

SELF POLISHING FOR MARBLE & GRANITE

Special liquid polisher for edges and bullnose.

Product description:

Relling zoni Super LUX Menang 23

Liquid product studied to polish and boost color of every stone material; it protects and polishes marbles, granites and stones edges. It makes a very thin and transparent polish film, that doesn't crack and doesn't turn yellow. Application of SUPERLUX makes unnecessary the following polishing of treated material. Its quick-drying formulation makes it the ideal product for an easy and fast job. SUPERLUX is particularly suitable to be used on angles and edges, frames and bullnose, deep enhancing color and brightness to material smoothed up to 800 grain.

Chemical characteristics:

Appearance	Liquid
Color	Clear transparent
Odor	Characteristic of solvent
Specific gravity at 20° C (68° F)	1,40±0,02
Hydro-solubility	Not soluble
pH	N.A.
Shelf life at 20°C (68° F)	24 months in original container
*	

 $^{st}\,$ indicative values, depending on the nature of the material and environmental conditions

Instruction for use

Surface must be clean and dry; stains, mildew, crusting must be scraped off otherwise they will be harder to remove. Application can be done by brush, by roller or by spray gun. It is suggested, when possible, to apply the product by cloth directly on the surface to be polished.

Application tools



Suggestion for use and recommendations:

- It is not advised to apply the product on synthetic materials as plastics, linoleum and laminate.
- Not suitable for use on pedestrian surfaces.
- Apply on clean and dry surfaces.
- Read carefully recommendations printed on label and perform a preliminary test on a small area before actual use.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.





Rev. 01/2015

TECHNICAL DATA SHEET (TDS)

Application surfaces

Marble, granite, terrazzo, agglomerated and stones.

Coverage

Pag | 2

For polishing of marble and granite polished or grinded above grit 800, with 1 kg (35 oz.) of product is possible to treat 60/70 sqm (650/750 sq.ft.)

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.bellinzoni.com

Packing

Item N°	Packing	Pcs
015AE3SL001	0,75 lt (25,37 fl.oz.)	12
015AE3SL004	4,00 lt (1,05 Gal)	3
015AE3SL020	20,00 lt (5,30 Gal)	1

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

H.S. Code

34.04.9000

Trademark and Origin of the good

BELLINZONI[®] is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product SUPERLUX is **MADE IN ITALY**.





DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.

